



# PTAC Made Simple



## Traditional experience, premium comfort

With **Distinctions** PTAC units, you have a reliable and high-quality option—while your guests enjoy ideal comfort.



Model	DCP 073A25AA	DCP 073A35AA	DCP 093A25AA	DCP 093A35AA	DCP 093A50AA	DCP 123A25AA	DCP 093A35AA	DCP 123A50AA	DCP 153A50AA	DCP 153A35AA
<b>Cooling</b>										
Voltage	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230
Capacity (BTU/h)	7,200 / 7,000	7,200 / 7,000	9,200 / 9,000	9,200 / 9,000	9,200 / 9,000	12,000 / 11,800	12,000 / 11,800	12,000 / 11,800	14,700 / 14,500	14,700 / 14,500
Amps	2.45 / 2.60	2.45 / 2.60	3.54 / 3.83	3.54 / 3.83	3.54 / 3.83	4.9 / 5.3	4.9 / 5.3	4.9 / 5.3	6.03 / 6.58	6.03 / 6.58
Watts	550 / 535	550 / 535	814 / 796	814 / 796	814 / 796	1,121 / 1,102	1,121 / 1,102	1,121 / 1,102	1,390 / 1,370	1,390 / 1,370
EER	13.1	13.1	11.3	11.3	11.3	10.7	10.7	10.7	10.6	10.6
CFM (cool/wet coil)	high	334	334	435	435	435	384	384	384	376
	low	236	236	341	341	341	311	311	311	315
CFM (dry)	high	334	334	435	435	435	384	384	384	376
	low	237	237	341	341	341	311	311	311	315
<b>Universal</b>										
Vent door CFM	61.1 / 57.6 / 50.6	61.1 / 57.6 / 50.6	61.1 / 57.6 / 50.6	61.1 / 57.6 / 50.6	61.1 / 57.6 / 50.6	62 / 60 / 56	62 / 60 / 56	62 / 60 / 56	62 / 60 / 56	62 / 60 / 56
Dehumidification (pints/hr.)	0.63	0.63	1.18	1.18	1.18	2.75	2.75	2.75	4.55	4.55
Net weight (lbs.)	101.63	101.63	98.1	98.1	98.1	108.69	108.69	108.69	113.1	113.1
Ship weight (lbs.)	112.43	112.43	108.69	108.69	108.69	119.49	119.49	119.49	122.8	122.8
CFM (dry)	334	334	435	435		384	384	384	376	376
<b>Electric Heat</b>										
Voltage	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230
Heater size (kW)	2.5	3.5	2.5	3.5	5	2.5	3.5	5	5	3.5
Heating capacity (BTU/h)	7,800 / 6,300	10,900 / 8,900	7,800 / 6,300	10,900 / 8,900	15,000 / 12,200	7,800 / 6,300	10,900 / 8,900	15,000 / 12,200	15,000 / 12,200	10,900 / 8,900
Watts	2,535 / 2,080	3,519 / 2,850	2,535 / 2,080	3,535.5 / 2,897	4,769 / 3,953	2,535 / 2,080	3,535 / 2,900	4,769 / 3,953	4,769 / 3,953	3,535 / 2,900
Amps	10.8 / 9.8	15.30 / 13.70	10.8 / 9.8	15.3 / 13.7	22 / 19.7	10.8 / 9.8	15.3 / 13.7	22 / 19.7	22 / 19.7	15.3 / 13.7



Model	DHP 093A25AA	DHP 093A35AA	DHP 093A50AA	DHP 123A25AA	DHP 123A35AA	DHP 123A50AA	DHP 153A35AA	DHP 153A50AA	DHP 094A35AA	DHP 124A35AA	
<b>Cooling</b>											
Voltage	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	265	265	
Capacity (BTU/h)	9,000 / 8,800	9,000 / 8,800	9,000 / 8,800	12,000 / 11,800	12,000 / 11,800	12,000 / 11,800	14,700 / 14,500	14,700 / 14,500	9,000	12,000	
Amps	3.46 / 3.75	3.46 / 3.75	3.46 / 3.75	5.0 / 5.4	5.0 / 5.4	5.0 / 5.4	6.03 / 6.58	6.03 / 6.58	3.01	4.31	
Watts	796 / 778	796 / 778	796 / 778	1,142 / 1,124	1,142 / 1,124	1,142 / 1,124	1,390 / 1,370	1,390 / 1,370	796	1,142	
EER	11.4	11.4	11.4	10.5	10.5	10.5	10.6	10.6	11.3	10.5	
CFM (cool/wet coil)	high	431	431	431	387	387	387	374	374	388	379
	low	333	333	333	309	309	309	312	312	321	313
CFM (dry)	high	431	431	431	387	387	387	374	374	388	380
	low	333	333	333	309	309	309	312	312	322	314
<b>Universal</b>											
Vent door CFM	61.1 / 57.6 / 50.6	61.1 / 57.6 / 50.6	61.1 / 57.6 / 50.6	62 / 60 / 56	62 / 60 / 56	62 / 60 / 56	62 / 60 / 56	62 / 60 / 56	61.1 / 57.6 / 50.6	62 / 60 / 56	
Dehumidification (pints/hr.)	1.06	1.06	1.06	2.81	2.81	2.81	4.29	4.29	1.06	2.81	
Net weight (lbs.)	102.51	102.51	102.51	115.96	115.96	115.96	116.84	116.84	101.19	113.1	
Ship weight (lbs.)	112.88	112.88	112.88	125.44	125.44	125.44	126.54	126.54	111.99	126.76	
<b>Electric Heat</b>											
Voltage	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	265	265	
Heater size (kW)	2.5	3.5	5	2.5	3.5	5	3.5	5	3.5	3.5	
Heating capacity (BTU/h)	7,800 / 6,300	10,900 / 8,900	15,000 / 12,200	7,800 / 6,300	10,900 / 8,900	15,000 / 12,200	10,900 / 8,900	15,000 / 12,200	10,900	10,900	
Watts	2,535 / 2,080	3,535.5 / 2,897	4,769 / 3,953	2,535 / 2,080	3,535 / 2,900	4,769 / 3,953	3,535 / 2,900	4,769 / 3,953	3,500	3,500	
Amps	10.8 / 9.8	15.3 / 13.7	22 / 19.7	10.8 / 9.8	15.3 / 13.7	22 / 19.7	15.3 / 13.7	22 / 19.7	13.46	13.46	
<b>Reverse Cycle</b>											
Voltage	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	265	265	
Capacity (BTU/h)	8,100 / 7,900	8,100 / 7,900	8,100 / 7,900	10,800 / 10,500	10,800 / 10,500	10,800 / 10,500	13,500 / 13,200	13,500 / 13,200	8,100	10,800	
Amps	3.04 / 3.28	3.04 / 3.28	3.04 / 3.28	4.3 / 4.6	4.3 / 4.6	4.3 / 4.6	5.38 / 5.82	5.38 / 5.82	3.1	4.3	
Watts	700 / 680	700 / 680	700 / 680	990 / 963	990 / 963	990 / 963	1,237 / 1,209	1,237 / 1,209	719	989	
COP	3.40	3.40	3.40	3.2	3.2	3.2	3.20	3.20	3.3	3.2	
CFM (dry)	431	431	431	387	387	387	374	374	388	380	



## Sales, Support and Service You Can Trust

**Five-Year Limited Warranty:** Enjoy one of the most comprehensive warranties in the industry: First Year: parts & labor; Second through fifth years: parts & labor on certain sealed system components; second through fifth years: on certain functional parts only. For complete warranty details, visit [www.distinctions-ptac.com](http://www.distinctions-ptac.com).

**Distinctions PTAC** are stocked and sold from the same warehouse as the **Amana® Brand PTAC** products you have come to love over the years.

## Features

**Dual Fan Motors:** Allows precise independent fan speed while providing quiet operation.

**LCDI Power Cord Included:** No need to match power cord type to unit size.

**3-Speed Fan:** Provide precise comfort control to your guests.

**Constant Fan:** Take advantage of each unit's dual options—select continuous fan operation or cycle the fan ON and OFF with the thermostat. Our 7-button design allows guests to select fan.

**Wired Thermostat Compatible:** Wire your PTAC with any standard thermostat for better temperature control

## Advantages

**Energy Efficiencies:** With EERs up to 13.1 and COPs up to 3.4, our unit's high efficiencies may qualify you for many of the rebates offered by electrical power companies.

**Automatic Emergency Heat:** No more “my unit is not heating” complaints during the middle of the night. Heat pump units will automatically switch over to electric resistance heat if the heat pump compressor system fails or if the heating load is greater than the unit capacity.

**Easy Pull-Out Filters:** Our filters are washable and easy to maintain.

**Condensate Dispersion System:** Our condensate dispersion system removes condensate from indoor cooling operation by throwing water directly on to the outdoor coil for rapid evaporation and increased cooling efficiencies.

**Call your Amana Brand PTAC sales representative at 800.647.2982 for complete details.**

Before purchasing this appliance, read important information available from your retailer about its estimated annual energy consumption, yearly operating cost or energy efficiency rating.

Amana® is a registered trademark of Maytag Corporation or its related companies and is used under license. All rights reserved.