



COMFORT IS BUILT-IN

- **Wired thermostat capable** to allow temperature control of the unit with our standard hardwired thermostats.
- **Electronic touch pad with remote control**
- **High energy efficiency with models up to 10.4 EER** saving you money when compared to lower EER models.
- **Easily removable condenser top** that allows for quick and complete cleaning of outdoor coils. This access for cleaning the outdoor coil enables easy removal of dirt and debris to help lengthen the life of the compressor and other system sealed components. Remove six easy access screws and let the cleaning begin.
- **Easy access slide out filter** has a permanent polypropylene filter mesh that is easy to remove and clean.
- **Accessory wall sleeve: PBWS01A** is a solid-sided, insulated metal sleeve. It includes a stamped aluminum exterior grille with a weather-seal rear enclosure for installation without the chassis. The sleeve has a solid bottom for complete weather-tight installation. An optional PBWMFC can be used when a more permanent weather seal is needed for sleeves installed without the chassis.
- **100% full factory run test** on all units for high reliability and dependability. Units start the first time—every time.
- **Quiet operation** designed with guest comfort in mind—providing reliable, quiet operation for years to come.
- **R32 Refrigerant** with 68% lower Global Warming Potential (GWP) and can reduce direct emissions from refrigerant by up to 73.6% as compared to R-410A

Model	Cooling Only Models				Electric Heat Models		Heat Pump Models			
	PBC-092J00AA	PBC-122J00AA	PBC-093J00AA	PBC-123J00AA	PBE-093J35AA	PBE-123J35AA	PBH-092J12AA	PBH-073J35AA	PBH-093J35AA	PBH-113J35AA
General Features										
Voltage	115	115	230 / 208	230 / 208	230 / 208	230 / 208	115	230 / 208	230 / 208	230 / 208
Approx. chassis weight	63 lbs	70 lbs	62 lbs	70 lbs	66 lbs	75 lbs	70 lbs	69 lbs	71 lbs	76 lbs
Approx. shipping weight	71 lbs	79 lbs	72 lbs	78 lbs	76 lbs	84 lbs	79 lbs	78 lbs	80 lbs	86 lbs
Temperature limiting	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Turbo mode	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Heat and cool fan cycle	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Cooling										
Capacity / BTUH	9,300	11,600	9,300 / 9,100	11,800 / 11,800	9,300 / 9,100	11,800 / 11,800	9,000	7,400 / 7,200	9,300 / 9,100	11,500 / 11,500
Amps	7.4	9.3	4.0	5.3	4.0	5.3	7.4	3.3	4.0	5.3
Watts	950	1,185	950 / 930	1,200 / 1,200	950 / 930	1,200 / 1,200	920	720 / 700	950 / 930	1,200 / 1,200
CFM	275	310	275	310	300	310	265	310	265	310
EER	9.8	9.8	9.8 / 9.8	9.8 / 9.8	9.8 / 9.8	9.8 / 9.8	9.8	10.3 / 10.3	9.8 / 9.8	9.6 / 9.6
CEER	9.7	9.7	9.7 / 9.7	9.7 / 9.7	9.7 / 9.7	9.7 / 9.7	9.7	10.3 / 10.3	9.6 / 9.6	9.5 / 9.5
Dehumidification - pts/hr	2.1	3.5	2.3	3.4	2.3	3.4	2.6	1.3	2.5	3.2
Electric Heat										
Capacity / BTUH	n/a	n/a	n/a	n/a	12,600 / 10,300	12,600 / 10,300	3,900 ⁺	12,600 / 10,300	12,600 / 10,300	12,600 / 10,300
Amps	n/a	n/a	n/a	n/a	16.1 / 14.5	16.1 / 14.5	11.0	16.1 / 14.5	16.1 / 14.5	16.1 / 14.5
Watts	n/a	n/a	n/a	n/a	3,700 / 3,030	3,700 / 3,030	1,150	3,700 / 3,030	3,700 / 3,030	3,700 / 3,030
Heat Pump (Reverse Cycle)										
Capacity / BTUH	n/a	n/a	n/a	n/a	n/a	n/a	8,500	6,700 / 6,600	8,300 / 8,200	10,500 / 10,400
Amps	n/a	n/a	n/a	n/a	n/a	n/a	7.4	3.3	4.0	5.3
Watts	n/a	n/a	n/a	n/a	n/a	n/a	830	655 / 645	810 / 800	1,060 / 1,150
COP	n/a	n/a	n/a	n/a	n/a	n/a	3.0	3.0	3.0 / 3.0	2.9 / 2.9
Thermostatic drain valve	n/a	n/a	n/a	n/a	n/a	n/a	Yes	Yes	Yes	Yes
Electrical Data										
NEMA plug configuration	5-15P	5-15P	6-15P	6-15P	6-20P	6-20P	5-15P	6-20P	6-20P	6-20P
Plug type	Parallel	Parallel	Tandem	Tandem	Perpendicular	Perpendicular	Parallel	Perpendicular	Perpendicular	Perpendicular
Power cord length	7.9' w/LCDI	7.9' w/LCDI	7.9' w/LCDI	7.9' w/LCDI	7.9' w/LCDI	7.9' w/LCDI	7.9' w/LCDI	7.9' w/LCDI	7.9' w/LCDI	7.9' w/LCDI

Features: (all models)

Agency approval	UL (Underwriters Laboratory) listed; USA and Canada
Chassis type	Slide-out for easy installation and service accessibility
Fan speeds	4 speeds: Turbo, high, medium and low
Fan ONLY	Yes - high, medium and low speed
Exhaust CFM	20
Discharge air	Top discharge with 3-way adjustable air throw
Slide-out-filter	Top pull-out polypropylene - permanent filter that is washable
Condensate	Yes, external drain spout on the PBWS01G-C optional wall sleeve drain spout
Low voltage interface for wired thermostat	Built-in


Dimensions:	Height	Width	Depth
Chassis dimensions	15 5/8"	26.0"	16 7/8"
With chassis installed	Depth with chassis installed and room front cover attached = 21 7/8"		
Sleeve cut-outs	15 13/16"	26 3/16"	Maximum wall thickness = 16 3/8"

All units meet or exceed 06-01-14 D.O.E. CEER minimums
Secondary heat source recommended to be used in conjunction with unit during electric heat operation

Optional Accessories:

PBWS01G-C	Insulated metal sleeve for installation of 26" built-in air conditioners; solid side and solid bottom with weather board and stamped aluminum grille.
PBAGK01TB	Architectural grille kit for use with PBWS01G-C sleeve and 26" built-in air conditioners in beige.
PBAGK01SB	Architectural grille kit for use with PBWS01G-C sleeve and 26" built-in air conditioners in custom colors
PBWMFC01A	An insulated metal cover for use when PBWS01G-C is installed without 26" built-in air conditioner
PBFAK01A	Sleeve adapter kit; converts Fedders BSAOOC & Friedrich WSC 27" wall sleeves for use with Amana 26" built-in air conditioners

Plug Type:



Note: Units ship without the optional PBWS01G-C wall sleeve and require a solid-side sleeve for field installation. If installing into existing sleeves, call your **Amana** brand sales person for compatibility assessment or adapter kits. Damage caused by improper sleeves, or by use of improper grilles, is not covered by the product warranty.

CALL YOUR **AMANA BRAND** PTAC SALES REPRESENTATIVE AT 800-647-2982 FOR FULL DETAILS.

Before purchasing this appliance, read important information available from your retailer about its estimated annual energy consumption, yearly operating cost or energy efficiency rating.

Wise decision,
It's an **AMANA** brand.